

# Standard Polypectomy Snares – Single Use



Oval

## Polypectomy Snare

Oval loop, monofilament wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-23-15-230	Oval	15	2.5	2.8	230
GPS-23-25-230	Oval	25	2.5	2.8	230
GPS-23-35-230	Oval	35	2.5	2.8	230



Oval



Oval Insulated tip

## Polypectomy Snare

Oval loop, braided wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-21-10-180	Oval	10	2.5	2.8	180
GPS-21-10-230	Oval	10	2.5	2.8	230
GPS-21-15-180	Oval	15	2.5	2.8	180
GPS-21-15-230	Oval	15	2.5	2.8	230
GPS-31-15-180	Oval Insulated Tip	15	2.5	2.8	180
GPS-31-15-230	Oval Insulated Tip	15	2.5	2.8	230
GPS-21-25-180	Oval	25	2.5	2.8	180
GPS-21-25-230	Oval	25	2.5	2.8	230
GPS-21-25-300	Oval	25	2.5	2.8	300
GPS-31-25-180	Oval Insulated Tip	25	2.5	2.8	180
GPS-31-25-230	Oval Insulated Tip	25	2.5	2.8	230
GPS-21-35-180	Oval	35	2.5	2.8	180
GPS-21-35-230	Oval	35	2.5	2.8	230
GPS-31-35-180	Oval Insulated Tip	35	2.5	2.8	180
GPS-31-35-230	Oval Insulated Tip	35	2.5	2.8	230
GPS-21-50-180	Oval	50	2.5	2.8	180
GPS-21-50-230	Oval	50	2.5	2.8	230



Medi-Globe polypectomy snares are directly compatible with Olympus electro-surgical generators. To verify compatibility with other electro-surgical generators, please, contact your Medi-Globe representative. Please refer to our “Accessories” leaflet.

# Polypectomy Snares

Single Use



### 360° Rotation

Enables easier polyp snaring

### Monofilament and Braided (Multifilament) Loop Versions

Precise and smooth cutting

### Loops with and without Insulated Tip

Protects perforation

L-GPS-SU-00-EN / LL-0029 Vers. 9.0 (12/2020)




### Medi-Globe GmbH

Medi-Globe-Straße 1–5 • D-83101 Rohrdorf OT Achenmühle  
 Tel.: +49 (0) 8032 973-379 • Fax: +49 (0) 8032 973-392  
 Email: sales@medi-globe.de • www.medi-globe.de

# Rotatable Polypectomy Snares – Single Use

# Standard Polypectomy Snares – Single Use

# Standard Polypectomy Snares – Single Use



## Polypectomy Snare

Oval loop, braided wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-01-15-180	Oval	15	2.5	2.8	180
GPS-01-15-230	Oval	15	2.5	2.8	230
GPS-11-15-180	Oval Insulated Tip	15	2.5	2.8	180
GPS-11-15-230	Oval Insulated Tip	15	2.5	2.8	230
GPS-01-25-180	Oval	25	2.5	2.8	180
GPS-01-25-230	Oval	25	2.5	2.8	230
GPS-11-25-180	Oval Insulated Tip	25	2.5	2.8	180
GPS-11-25-230	Oval Insulated Tip	25	2.5	2.8	230
GPS-01-35-180	Oval	35	2.5	2.8	180
GPS-01-35-230	Oval	35	2.5	2.8	230
GPS-11-35-180	Oval Insulated Tip	35	2.5	2.8	180
GPS-11-35-230	Oval Insulated Tip	35	2.5	2.8	230



## Polypectomy Snare

Hexagonal loop, braided wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-02-25-180	Hexagonal	25	2.5	2.8	180
GPS-02-25-230	Hexagonal	25	2.5	2.8	230



## Polypectomy Snare

Hexagonal loop, braided wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-22-25-180	Hexagonal	25	2.5	2.8	180
GPS-22-25-230	Hexagonal	25	2.5	2.8	230
GPS-32-25-180	Hexagonal Insulated Tip	25	2.5	2.8	180
GPS-32-25-230	Hexagonal Insulated Tip	25	2.5	2.8	230
GPS-22-35-180	Hexagonal	35	2.5	2.8	180
GPS-22-35-230	Hexagonal	35	2.5	2.8	230
GPS-32-35-180	Hexagonal Insulated Tip	35	2.5	2.8	180
GPS-32-35-230	Hexagonal Insulated Tip	35	2.5	2.8	230



## Polypectomy Snare

Asymmetrical loop, braided wire

Catalogue No.	Loop Shape	Loop Diameter (mm)	Sheath Diameter (mm)	Min. Accessory Channel (mm)	Working Length (cm)
GPS-41-15-230	Asymmetrical	15	2.5	2.8	230
GPS-41-25-230	Asymmetrical	25	2.5	2.8	230

